bimos

characteristics Unitec 3 with glides and footring

Article: 9651 integral foam

Dimensions in mm

| | Seat: | H: | 580-850 |
|--------------|------------------|----------|--------------|
| | | | |
| Packing data | Weight Volume | kg m³ | 14,0 0,15 |



| Base equipment | | Benefit |
|--------------------------|---|--|
| Backrest | Large, ergonomically designed backrest to take the strain off the spine and muscles with integrated lumbar support. | Healthy posture due to a hump providing support for the back in the lumbar region. |
| | Backrest height adjustment convenient and easy to handle in sitting position. | The support area can be adapted in accordance to the user's body size. |
| Seat | Ergonomically designed seat with rounded front edge. | The round front edge of the seat prevents blocked circulation in the thighs. |
| Seat and backrest design | Integral foam (PU): | The use of integral foam is recommended for work |
| | The new developed SoftTouch integral foam provides the ultimate softness in seating, is washable and resistant to external influences Colour: Black (2000) | environments where the chair is in contact with aggressive substances and sharp parts. |
| Seat height | Stepless seat height setting from 580 - 850 mm supported by safety gas spring with protective cover. Using stop-and-go-castors, the seat height increases by 4 cm. | Seat height can be adapted to nearly 95 % of all body sizes, the cover protects the gas spring from dust and dirt. |
| Technology | Permanent contact-backrest | This mechanism ensures that the backrest responds immediately to any movements of the upper body by following them. Thus, the back remains supported all the time.The backrest can also be locked into any tilt position if required. |
| | Quick adjustment | Every function can be operated comfortable and easy in sitting position. |
| Base | Black 5 star base made from plastic. Flat design. | Very high stability, longevity and safety Flat design prevents stumbling hazard. |
| Glides | Wearproof plastic glides with a large surface Area. | Offer a superb level of stability. |
| Foot ring | Chrome-plated foot ring, adjustable in height. | Provides support through the wide tread area and can be easily and quickly adjusted in height. |
| Materials | The materials used are recyclable. | Environmentally friendly. |

bimos

characteristics Unitec 3 with glides and footring

Article: 9651 integral foam

| Dimensions in mm | Seat: | H: | 580-850 | |
|------------------|--------|-----------|---|---|
| Packing data | Weight | kg | 14,0 | |
| | Volume | m³ | 0,15 | |
| Standards | | DIN 68 87 | | Procuring is insured. |
| | | | S "safety tested" mark of confirmity | |
| | | - | Quality Management System DIN EN ISO 9001 Regulation EWG Nr. 1836/93 and | |
| | | Environme | | |
| | | | ent System DIN ISO 14001. | |
| Warranty | | | ng term warranty, 3 years full | Guaranteed quality and high efficiency. |
| | | warranty. | | |
| | | | | |

bimos

characteristics Unitec 3 with glides and footring

Article: 9651 integral foam

Dimensions in mm

| | Seat: | H: | 580-850 |
|--------------|------------------|----------|--------------|
| | | | |
| Packing data | Weight Volume | kg m³ | 14,0 0,15 |



Benefit

Options

Armrests Loop armrest Made of polyar Multifunctional armrest The armrests a to suit the indiv

Made of polyamide, adjustable in width (20 mm). The armrests are adjustable in height, width and depth to suit the individual user.